



TRITO 50

LABELLER HEAD - MAX. LABEL WIDTH 50 MM



DESCRIPTION

Automatic self-adhesive label applicator to be coupled with production lines, ideal for application on flat or slightly uneven products. The TRITO labeller head can be used for applying labels to the top or sides of products. Main feature of the TRITO model is the simplicity of installation and use. The TRITO Head is available in the right or left hand version.

TECHNICAL FEATURES

Speed	variable from 0-30 m
Max. label width	50 mm



Min. label width	10 mm
Max. label length	500 mm (other measurements upon request)
Min. label length	10 mm
Min. internal reel diameter	38 mm (76 with adapter)
Max. external reel diameter	300 mm
Motor type	stepper

minipack@-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

PLUS

- Electronic control unit managed by a microprocessor with display, possibility of controlling the delivery speed, start delay, label pre-distribution, piece counter
- Start photocell
- Label reading by photocell
- Power supply voltage – 220 or 110 V 50/60 Hz
- Weight – 15 kg

OPTIONAL FEATURES

- Hot/dry printing for printing batch and date
- Encoder 1000 pulses with encoder control unit
- Control unit for 60 m/min speed
- Reel end paper break optical/acoustic alarm
- Pre reel end alarm
- Support column with base
- Self-locking wheels
- Special photocell for transparent labels



TRITO 100

LABELLER HEAD - MAX. LABEL WIDTH 100 MM



DESCRIPTION

Automatic self-adhesive label applicator to be coupled with production lines, ideal for application on flat or slightly uneven products. The TRITO labeller head can be used for applying labels to the top or sides of products. Main feature of the TRITO model is the simplicity of installation and use. The TRITO Head is available in the right or left hand version.

TECHNICAL FEATURES

Speed	variable from 0-30 m
Max. label width	100 mm

minipack@torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



Min. label width	10 mm
Max. label length	500 mm (other measurements upon request)
Min. label length	10 mm
Min. internal reel diameter	38 mm (76 with adapter)
Max. external reel diameter	300 mm
Motor type	stepper

minipack@-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

OPTIONAL FEATURES

- Hot/dry printing for printing batch and date
- Encoder 1000 pulses with encoder control unit
- Control unit for 60 m/min speed
- Reel end paper break optical/acoustic alarm
- Pre reel end alarm
- Support column with base
- Self-locking wheels
- Special photocell for transparent labels

PLUS

- Electronic control unit managed by a microprocessor with display, possibility of controlling the delivery speed, start delay, label pre-distribution, piece counter
- Start photocell
- Label reading by photocell
- Power supply voltage – 220 or 110 V 50/60 Hz
- Weight – 15 kg