

BATTERY POWERED STRAPPING TOOL FOR PET/PP STRAPP



Features		Model No : ZP 93	
<ul style="list-style-type: none"> Automatic Tension & Friction Welding Operation Lever for easy strap feeding & easy tool removal Bosh 18V Li-on Battery Pre-programmed Control Panel Brushless Motor Impact resistant protection 			
Technical Specifications			
<ul style="list-style-type: none"> Strap Width 		<ul style="list-style-type: none"> 12-16 mm 	
<ul style="list-style-type: none"> Strap Thickness 		<ul style="list-style-type: none"> Up to 1.2 mm 	
<ul style="list-style-type: none"> Maximum Tension 		<ul style="list-style-type: none"> 250 Kgs (2500N) 	
<ul style="list-style-type: none"> Sealing Efficiency 		<ul style="list-style-type: none"> 85 % +/- 5 % 	
<ul style="list-style-type: none"> Strap Apply 		<ul style="list-style-type: none"> PET Strap/*PP Strap 	
<ul style="list-style-type: none"> Make 		<ul style="list-style-type: none"> Made in Taiwan 	
Other Information			
<ul style="list-style-type: none"> Battery Life Cycle 		<ul style="list-style-type: none"> : Approx. 2000 Charges (Based on proper charging & discharging operation) 	
<ul style="list-style-type: none"> Bosh Charging Time 		<ul style="list-style-type: none"> : 30 Minutes under normal condition 	
<ul style="list-style-type: none"> Strapping Cycles 		<ul style="list-style-type: none"> : 450 – 600 cycles for brand new & fully charged battery 	
Packing Details			
<ul style="list-style-type: none"> Tool equipped with : 1 Li-Ion Battery, 1 Bosh Charger, Cleaning Brush, Strap width adjustment kit, Control panel cover & user Manual 			
<ul style="list-style-type: none"> Carton Dimensions 		<ul style="list-style-type: none"> L- 16.5 x W- 12 x H -7 (Inches) 	
<ul style="list-style-type: none"> Tool Weight 	<ul style="list-style-type: none"> 3.5 Kgs 	<ul style="list-style-type: none"> Total Weight 	<ul style="list-style-type: none"> 6 Kgs
Note:			
<ol style="list-style-type: none"> Tension performance, Sealing efficiency, & number of strapping cycle are based on Strap Quality, Strap Specification, Setting Tension & remaining of battery power. If using PP Strap , Strap has to be of Virgin quality with Thickness not less than 0.7 mm 			
Warranty : 1 Years warranty only on Motor & PCB,Warranty is not applicable on wearing parts			
			
			